



Binding Pillar

Series CZ2000 -3



Products Features

- CZ2000/1-BA7 Switch modules have 2P or 4P for options, can be used together with 11 different operation heads (pushbuttons, switches, key operated switches, E-stop pushbuttons).
- CZ2000/1-BB7 control switch module, available in 2P~12P control functions.
- CZ2000/1-BD7 Signal lamp module, LED light source, four voltage ratings, five colors in red, green, yellow, white, blue are available.
- CZ2000/1-BG7 Light-control switch module, can be applied to Ex d or Ex e enclosure.
- CZ2000/1-BP7 Flameproof potentiometer module, 100Ω~2MΩ, Max 0.1W.
- CZ2000/1-B□ switch handle, to operate the switch modules 63A, 100A, 250A, 400A, 630A from the front. or to operate the switch modules 100A, 250A from the side.
- CZ2000/1-BW7 observation window for instruments φ64mm, φ89mm.
- CZ2000/1-BI7 observation and operation window for instruments, window have four sizes.
- CZ2000/2A Flameproof cable bushing, thread size M16 to M80, conductor size 0.5mm²-120mm².
- CZ2000/2B Flameproof cable bushing, thread M50, conductor size 0.5mm²-120mm², to be used for the connection of two Ex d enclosures.
- CZ2000/3 Flameproof binding pillar, thread M42, wiring capacity 50mm²-240mm².
- International IECEx approval, European union ATEX certifications (U).
- Accessories: special spanner, label, safety latch.



فرست اوتوماشن

Binding Pillar

Series CZ2000 -3



Product Parameter

Product type:	Flameproof binding pillar
Certification:	IECEX ATEX
Application range (zones):	2G/Gb/zone 1
Min.ambient temperature:	-55°C
Max.ambient temperature:	+60°C
Min.service temperature:	-55°C
Max.service temperature:	+100°C
Degree of protection:	IP66
Rated voltage:	up to 1000V AC
Rated current:	max. 630A
Flameproof thread:	M42×1.5





فرست اوتوماشن

Binding Pillar

Series CZ2000 -3



Illustration

Order No.



CZ2000/3-M42 01

CZ2000/3-M42 02

Contact

info@first-automation.com.eg/ • 01101619222 – 01100200886 • <https://first-automation.com.eg/>



فرست اوتوماشن

Binding Pillar

Series CZ2000 -3

